

**Amendments to the Claims**

Please cancel Claims 2, 3, 10, 11, 16, 17 and 24. Please amend Claims 1, 7, 8, 9, 12, 15, 18, 22 and 23. The Claim Listing below will replace all prior versions of the claims in the application:

**Claim Listing**

1. (Currently amended) A method for switching from a reserved first path between a source node and a destination node, the reserved first path comprising one or more interconnected nodes, to a reserved second path comprising one or more interconnected nodes comprising the steps of:

enabling the second path for data transfer between the source node and destination node; and

disabling the first path for data transfer between the source node and the destination node after enabling the second path for data transfer;

wherein the step of enabling further comprises:

determining the nodes and links shared by the second path and the first path; and  
reserving resources in the second path not shared with the first path;

wherein the step of determining further comprises:

comparing a path identification field value and a tunnel session identification field  
value in a path message for the second path with the path identification field value and  
the tunnel session identification field value in the reserve message for the first path.

2. Canceled

3. Canceled

4. (Original) A method as claimed in Claim 1 wherein the step of reserving further comprises:

sending a path message for the second path to the destination node; and

sending a reserve message for the second path to the source node in response to the path message sent to the destination node.

5. (Original) A method as claimed in Claim 1 wherein the step of disabling further comprises:

releasing resources in the first path not shared with the second path.

6. (Original) A method as claimed in Claim 5 wherein the step of releasing further comprises:

sending a request release message for the first path by the source node to the destination node.

7. (Currently amended) A method as claimed in Claim 1 A method for switching from a reserved first path between a source node and a destination node, the reserved first path comprising one or more interconnected nodes, to a reserved second path comprising one or more interconnected nodes comprising the steps of:

enabling the second path for data transfer between the source node and destination node;  
and

disabling the first path for data transfer between the source node and the destination node  
after enabling the second path for data transfer wherein the step of enabling in an intermediate  
node comprises the steps of:

receiving a path message from an upstream node;

sharing resources with the first path dependent on a tunnel session and tunnel path identification in the path message; and

forwarding the path message to a downstream node.

8. (Currently amended) A method as claimed in Claim 1 A method for switching from a reserved first path between a source node and a destination node, the reserved first path comprising one or more interconnected nodes, to a reserved second path comprising one or more interconnected nodes comprising the steps of:

enabling the second path for data transfer between the source node and destination node;  
and

disabling the first path for data transfer between the source node and the destination node  
after enabling the second path for data transfer wherein the step of disabling in an intermediate  
node comprises the steps of:

receiving a path tear message from an upstream node;  
releasing resources for the first path dependent on a tunnel session identification and  
tunnel path identification in the path message; and  
forwarding the path tear message to a downstream node.

9. (Currently amended) An apparatus for switching from a reserved first path between a source node and a destination node, the reserved first path comprising one or more interconnected nodes, to a reserved second path comprising one or more interconnected nodes comprising:

a path switch routine;  
means, within the path switch routine, for enabling the second path for data transfer between the source node and the destination node; and  
means, within the path switch routine, for disabling the first path for data transfer between the source node and the destination node after the second path is enabled for data transfer;

wherein the means for enabling further comprises:  
means for determining the nodes and links shared by the second path and the first path;  
and  
means for reserving resources in the second path not shared with the first path, and  
wherein the means for determining further comprises:  
means, within the path switch routine, for comparing a path identification field value and  
a tunnel session identification field value in a path message for the second path with the path  
identification field value and the tunnel session identification field value in the path message for  
the first path.

10. Canceled

11. Canceled

12. (Currently amended) An apparatus as claimed in Claim 9 ~~10~~ wherein the means for reserving further comprises:

means, within the path switch routine, for sending a path message for the second path by the source node to the destination node; and

means, within the path switch routine, for sending a reserve message for the second path by the destination node to the source node after the destination node has received the path message.

13. (Original) An apparatus as claimed in Claim 9 wherein the means for disabling further comprises:

means, within the path switch routine, for releasing resources in the first path not shared with the second path.

14. (Original) An apparatus as claimed in Claim 13 wherein the means for releasing further comprises:

means, within the path switch routine, for sending a release message for the first path by the source node to the destination node.

15. (Currently amended) An apparatus for switching from a reserved first path between a source node and a destination node, the reserved first path comprising one or more interconnected nodes, to a reserved second path comprising one or more interconnected nodes comprising:

a path switch routine responsive to a request for switching from the first path to the second path, the path switch routine further comprising:

an enable routine which enables the second path for data transfer between the source node and the destination node; and

a disable routine which disables the first path for data transfer between the source node and the destination node after the enable routine has enabled the second path for data transfer,  
wherein the enable routine further comprises:

a shared node detection routine which determines the nodes and links shared by the second path and the first path; and

a reserve resources routine which reserves resources in the second path not shared with the first path,

wherein the shared node detection routine further comprises:

a compare routine which compares a path identification field value and a tunnel session identification field value in a path message for the second path with the path identification field value and the tunnel session identification field value in the path message for the first path.

16. Canceled

17. Canceled

18. (Currently amended) An apparatus as claimed in Claim 16 15 wherein the reserve resources routine further comprises:

a path message routine which sends a path message for the second path from the source node to the destination node; and

a reserve message routine which sends a reserve message for the second path from the destination node to the source node in response to the path message sent by the request path message routine.

19. (Original) An apparatus as claimed in Claim 18 wherein the path message comprises:  
a session identification identifying a tunnel; and  
a tunnel path identification identifying a tunnel path for the tunnel.

20. (Original) An apparatus as claimed in Claim 19 wherein the disabling routine further comprises:

a release resources routine which releases resources in the first path not shared with the second path.

21. (Original) An apparatus as claimed in Claim 15 wherein the release resources routine further comprises:

a request release message routine which sends a release message for the first path to the destination node.

22. (Currently amended) An apparatus as claimed in Claim 15 An apparatus for switching from a reserved first path between a source node and a destination node, the reserved first path comprising one or more interconnected nodes, to a reserved second path comprising one or more interconnected nodes comprising:

a path switch routine responsive to a request for switching from the first path to the second path, the path switch routine further comprising:

an enable routine which enables the second path for data transfer between the source node and the destination node; and

a disable routine which disables the first path for data transfer between the source node and the destination node after the enable routine has enabled the second path for data transfer  
wherein the enable routine in the intermediate node comprises:

a path message receive routine for receiving a path message from an upstream node;

a session-path routine for sharing resources with the first path dependent on a tunnel session and tunnel path identification in the path message; and

a path message forward routine for forwarding the path message to a downstream node.

23. (Currently amended) A method as claimed in Claim 15 An apparatus for switching from a reserved first path between a source node and a destination node, the reserved first path comprising one or more interconnected nodes, to a reserved second path comprising one or more interconnected nodes comprising:

a path switch routine responsive to a request for switching from the first path to the second path, the path switch routine further comprising:

an enable routine which enables the second path for data transfer between the source node and the destination node; and

a disable routine which disables the first path for data transfer between the source node and the destination node after the enable routine has enabled the second path for data transfer  
wherein the disable routine in an intermediate node comprises:

a receive path tear message routine for receiving a path tear message from an upstream node;

a release resources routine for releasing resources for the first path dependent on a tunnel session identification and tunnel path identification in the path message; and

a forward path tear message routine for forwarding the path tear message to a downstream node.

24. Canceled